

bis 1'350 N Belastung
up to 1'350 N load

**Ab Lager lieferbar!
Available from stock!**

**Technische Daten
Technical Data**

PSG22	6000 [mm]	Max. Schienenlänge PSG Max. length rail PSG	6000 [mm]	PSG33
	5.2 x 8 [mm]	Grösse Schlitzbohrung Size slot drilling	6.2 x 10 [mm]	
	z.B. M4 Linsenschrauben ISO 7380 p.ex. M4 oval-head screw ISO 7380	Befestigungsschrauben Fixing Screws	z.B. M5 Linsenschrauben ISO 7380 p.ex. M5 oval-head screw ISO 7380	
	80 [mm]	Lochabstand Pitch	80 [mm]	
	40 / 80 / ... / 40 [mm]	Standard Bohrbild Standard hole pattern	40 / 80 / ... / 40 [mm]	
	0.656 [kg]	Gewicht Schiene pro lfm Weight rail per rm	1.195 [kg]	
Standardlängen L (mm) Standard length L (mm)				
240-320-400-480-560-640-720-800-880-960-1040-1120-1200-1280-1360-1440-1520-1600-1680-1760-1840-1920-2000-2080-2160-2240-2320-2400-2480-2560-2640-2720-2800-2880-2960-3040-3120-3200-3280-3360-3440-3520-3600-3680-3760-3840-3920-4000-4080-4160-4240-4320-4400-4480-4560-4640-4720-4800-4880-4960-5040-5120-5200-5280-5360-5440-5520-5600-5680-5760-5840-5920-6000				
Sonderlängen erhältlich, fragen Sie uns an! Special lengths available, ask us for more!				

